

Worldwide Sales since 1957

AW Dynamometer, Inc. 800-447-2511 | sales@awdynamometer.com

HYDRAULIC SCISSOR LIFT TABLES



OPERATING FEATURES:

- Lubricated for life, maintenance free bearings at pivot points
- Scissor legs are solid high-tensile steels, one-piece construction with precision reamed holes for accurate alignment and table operation
- ✓ Reservoir is filled with oil
- ✓ Pre-wired motor controls (NEMA12)
- ✓ Pre-wired push buttons (NEMA12)
- ✓ Primary control Standard push button control on 10ft. cord
- Hydraulic velocity fuse Prevents free fall if hydraulic hose is severed

HYDRAULIC SCISSOR LIFT TABLES

AW Dynamometer offers four models of heavy-duty hydraulic scissor lift tables. These tables are reinforced with a 1/2" steel base plate and a 1" steel top plate. The 4 pole design allows the top plate with welded cylinders to move freely for vertical movement and provide additional locking capacity when the desired height is achieved. The customer can choose whether to mount the dynamometer or the motor on the lift table. If motor mounting is preferred, AW provides T-slots with a motor mounting plate and NEMA bolt patterns. All models come standard with accordion bellows, which consist of steel-reinforced vinyl barrier which expands and retracts with the movement of the table. The accordion bellows enclose the internal components of the equipment.



Worldwide Sales since 1957

AW Dynamometer, Inc. 800-447-2511 | sales@awdynamometer.com

HYDRAULIC SCISSOR LIFT TABLES

MODELS

HSLT 1500X

- √ 1,500 lifting capacity
- ✓ Platform size: 48" x 48"
- Collapsible height: 11"
- ✓ Travel: 36"
- Raised height: 47"
- Power unit: 1 1/2 HP, 115V, single phase, 60hz
- ✓ Shipping weight: 2,640lbs

HSLT 2500X

- ✓ 2,500 lifting capacity
- ✓ Platform size: 48" x 48"
- ✓ Collapsible height: 11"
- **✓** Travel: 36"
- ✓ Raised height: 47"
- ✓ Power unit: 1 1/2 HP, 230-460V, three phase, 60hz
- ✓ Shipping weight: 2,760lbs

HSLT 6000X

- √ 6,000 lifting capacity
- ✓ Platform size: 48" x 60"
- ✓ Collapsible height: 11"
- ✓ Travel: 36"
- ✓ Raised height: 47"
- ✓ Power unit: 1 1/2 HP, 230-460V, three phase, 60hz
- ✓ Shipping weight: 2,800lbs

HSLT 8000X

- √ 8,000 lifting capacity
- ✓ Platform size: 48" x 84"
- ✓ Collapsible height: 16"
- ✓ Travel: 50"
- ✓ Raised height: 66"
- ✓ Power unit: 1 1/2 HP, 230-460V, three phase, 60hz
- ✓ Shipping weight: 5,400lbs